

Hornos convención con controles electromecánicos



mod. 6GL-C-8



mod. F40G-C-8

mod.	mm.	O - GN			kW	Volt Hz 50	mm.	mm.	mm.
		q.ty	kW	Σ kCal/h					
6GL-C-8	870x745x842H	6 GN1/1	14,0	12.040	0,3	230/1N+T	78	130	0,80
10G-C-8	940x997x1.082H	10 GN1/1	19,0	16.340	0,3	230/1N+T	70	170	1,30
F2011G-C-8	970x997x1.906H	20 GN1/1	30,0	25.800	0,6	230/1N+T	70	460	3,4
F20G-C-8	1.220x998x1.096H	10 GN2/1-20 GN1/1	22,0	18.986	0,5	230/1N+T	70	245	2,0
F40G-C-8	1.220x997x1.900H	20 GN2/1-40 GN1/1	50,0	43.000	1,0	230/1N+T	70	650	4,5

Comandi elettromeccanici | Electromechanical controls | Commandes électromécaniques
 Elektromechanische Steuerungen | Comandos electromecánicos

Hornos convención con controles electromecánicos



mod. 6EL-C-8



mod. F40E-C-8

O - GN

mod.	mm.	 q.ty	 kW	 kW	Σ  kW	Volt Hz 50	 mm.		
6EL-C-8	870x745x842H	6 GN1/1	9	0,3	9,3	400/3N+T	78	120	0,80
10E-C-8	940x997x1.082H	10 GN1/1	15	0,3	15,3	400/3N+T	70	145	1,30
F2011E-C-8	970x997x1.900H	20 GN1/1	30	0,6	30,6	400/3N+T	70	425	3,4
F20E-C-8	1.220x998x1.096H	10 GN2/1-20 GN1/1	21	0,5	21,5	400/3N+T	70	225	2,0
F40E-C-8	1.220x997x1.900H	20 GN2/1-40 GN1/1	42	1	43	400/3N+T	70	550	4,5

Comandi elettromeccanici | Electromechanical controls | Commandes électromécaniques | Elektromechanische Steuerungen | Comandos electromecánicos