

Sanwicheras



mod. TM-L



mod. TM-R



mod. TD-L



mod. TD-LR



mod. TD-R



Tostiera
Kontaktgrille



Toaster
Tostador



Toasteur

mod.	mm.	Superficie utile Working surface Surface utile Nutzfläche	V - Hz	W	°C		
TM-L	380x435x235H	355x255	230/1N+T 50/60 Hz	2100	300	23	0,04
TM-R	380x435x235H	355x255	230/1N+T 50/60 Hz	2100	300	23	0,04
TD-R	515x435x235H	500x255	230/1N+T 50/60 Hz	3000	300	30	0,06
TD-LR	515x435x235H	500x255	230/1N+T 50/60 Hz	3000	300	30	0,06
TD-L	515x435x235H	500x255	230/1N+T 50/60 Hz	3000	300	30	0,06

L = liscio | smooth | lisse | glatt | liso
 R = rigato | grooved | rainurée | gerillt | rayado
 LR = liscio rigato | smooth grooved | lisse rainurée | glatt-gerillt | liso rayado

- Piastre in ghisa con trattamento di vetroceramicatura:
 - cast iron plates with ceramic coating treatment:
 - Plaques en fonte avec traitement vitrocéramique:
 - Gusseisenplatte mit keramischer Beschichtung :

Tostiera



mod. TM-V-LL



mod. TM-V-LR



mod. TM-V-RR



Piastre vetroceramica

Kontaktgrille mit Ceranplatte





Glass ceramic plates

Vidriocerámica



Plaque en vitro ceramique

mod.	mm.	Superficie utile Working surface Surface utile Nutzfläche	V - Hz	W	°C		
TM-V-LL	435x490x170H	340x290	230/1N+T 50/60 Hz	3000	300	16	0,06
TM-V-LR	435x490x170H	340x290	230/1N+T 50/60 Hz	3000	300	16	0,06
TM-V-RR	435x490x170H	340x290	230/1N+T 50/60 Hz	3000	300	16	0,06
TD-V-LL	700x490x170H	(260x290) x 2	230/1N+T 50/60 Hz	3000	300	25	0,12
TD-V-LR	700x490x170H	(260x290) x 2	230/1N+T 50/60 Hz	3000	300	25	0,12

LL = liscio | smooth | lisse | glatt | liso

RR = rigato | grooved | rainurée | gerillt | rayado

LR = liscio rigato | smooth grooved | lisse rainurée | glatt-gerillt | liso rayado